

PRODUCT REFERENCE:**565 CLEAR**

DESCRIPTION: High mass acrylic tape with red HDPE film liner. The product has excellent joint movement capability and impact resistance. It is optically clear and has good solvent resistance.

ADHESIVE DATA

	<u>AVERAGE VALUES</u>	<u>TEST METHOD</u>
Peel (N/25mm) 23°C 70°C	>30 N/25mm >15 N/25m	AFERA 4001 FTM 8
Shear on stainless steel 10N – 25mm x 25mm (hours)		
23°C	>500 Hours	AFERA 4012
70°C	>200 Hours	

CARRIER

Tensile	62N/cm	DIN 53455
Elongation (%) At Break	>300%	DIN 53455
Density (approximately)	900kg/m3	

RELEASE LINER

Red HDPE Film 80 Microns

HEAT RESISTANCE

Minimum application temperature +10°C
End use temperature range -40°C to +120°C
Short Term +180°C

THICKNESS AVAILABLE

0.25/ 0.5, 1.0, 1.5, 2MM
3MM By special order

NOTE

All technical data is based on average values. Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for his intended use and the user assumes all risk and liability whatsoever in connection therewith.